



SEAWORTHY RIPPER

- Reliable Performance
- Exceptional Vibration Resistance
- Improved Semi Cycling Ability, Higher Reserve Capacity
- Reliable Starting & Longer Service Life
- Up to 24 Months Warranty



* Conditions apply



1. Re-engineered Container and Cell Design

Made more durable, delivering tight-fitting elements and better channeling of residue preventing short circuits and improving vibration resistance.

2. Dura Connectors

Re-engineered lead connectors, facilitate a more efficient current flow to deliver maximum capacity and better durability. Improved process design, provides stronger plate assembly bonding for better vibration resistance and longer service life.

3. Expanded Calcium Grids

The construction of the Calcium plates in super compressed rolled strips creates a dense grid pattern allowing for a more compact unit, less vulnerable to heat & corrosion delivering efficient cranking power.

4. Higher Density Paste Formulation

Specially formulated paste, improving semi-cycling ability, higher RC, holds charge longer, giving the benefits of superior performance and outstanding durability.

5. PE Ultra Separator

Increased separator thickness, improving strength, offering superior puncture resistance and exceptional durability.

6. Flame Eliminator

Specially designed Unified Flame Eliminator, provides protection from explosions triggered by external ignition sources.

7. Fold Down Carry Handle

Easy to use fold down carry handle, provides ergonomic handling as well as tucks in flush with the battery lid for safe and hassle free installation.

8. Hydro Eye

Built in charge indicator, providing a convenient read of the battery's condition.

9. Twin Terminals

Provides convenient and safe electrical connections for both starting application and accessory attachments.

10. Pure Electrolyte

Allows Improved battery charge ability, delivering higher capacity and allowing the use of more accessories for longer time.

SeaMaster

TYPE	NOMINAL VOLTAGE V	MCA @ 0°C	CCA @ (-18°C)	RC @ 25°C	AH @ 20HR	OVERALL DIMENSION (mm)				WET WEIGHT (kg)	ASSEMBLY	POST TYPE	OTHER FEATURES	WARRANTY
						L	W	H	TH					
SEAMASTER – STARTING MAINTAINABLE														
M50	12	730	585	130	70	259	173	201	222	17.3	D	DST	ACC,EL,RPH	18
M70	12	825	660	160	75	304	173	203	224	21.4	D	DST	ACC,NL,FDH	18
SEAMASTER GOLD – STARTING MAINTENANCE FREE														
MFM48	12	720	575	105	60	233	173	182	221	15.8	D	DFA	CV,EL&FL,FDH,HE	24
MFM50	12	800	640	140	80	259	173	202	222	18.2	D	DST	CV,FL,RPH,HE	24
MFM70	12	900	720	160	85	304	173	203	224	22.0	D	DST	CV,FL,RPH,HE	24
MFM87	12	1000	800	200	110	330	172	215	236	29.0	D	DST	CV,NL,FDH,HE	12

ABBREVIATIONS & BATTERY ASSEMBLIES

CV	Central Venting	FL	Front Ledge
DFA	Dual Fit Aligned Terminals	HE	Hydrometer Eye
DST	Dual System Terminals	ACC	Accessible
EL	End Ledge	RPH	Rope Handles
FDH	Fold Down Handles		

