



FT12-125(12V125Ah)

Specification




Cells Per Unit	6
Voltage Per Unit	12V
Nominal Capacity	125Ah@10hour-rate to 1.80V per cell @25°C
Weight	Approx. 36.0 Kg (Tolerance ±5.0%)
Internal Resistance	≤4.5 mΩ (Full Charge Condition @25°C)
Terminal	Default F9(M8)
Max. Discharge Current	1250A (5 sec)
Design Life	12 years
Max. Charging Current	37.5 A
Reference Capacity	C ₃ 93.9Ah C ₅ 106.0Ah C ₁₀ 125.0Ah C ₂₀ 132.4Ah
Standby Use Voltage	13.6 V~13.8 V @ 25°C Temperature Compensation: -3mV/°C/Cell
Cycle Use Voltage	14.6 V~14.8 V @ 25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -20°C~60°C Charge: 0°C~50°C Storage: -20°C~60°C
Normal Operating Temperature Range	25°C ±5°C
Self Discharge	RITAR Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C and then recharging is recommended. Monthly Self-discharge ratio is less than 3% at 25°C. Please charge batteries before using.
Container Material	A.B.S. UL94-V0



FT(Front Terminal) Series is specially designed for telecom use with 12 years design life in float service. By adopting a new AGM separator and centralized venting system, the battery can be installed in any position while maintaining high reliability. The dimensions of the FT series are designed for 19" and 23" cabinet installation. It is suitable for telecom EPS/EPS, applications.



Dimensions



Length	551±2mm (21.7 inches)
Width	109±2mm (4.29 inches)
Height	239±2mm (9.41 inches)
Total Height	239±2mm (9.41 inches)
Terminal	Value
M5	6~7 N*m
M6	8~10 N*m
M8	10~12 N*m

Unit: mm

Constant Current Discharge Characteristics : A (25°C)

F.V/Time	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	215.7	134.1	76.4	45.5	35.3	27.7	23.6	15.8	13.2	6.90
1.65V	206.2	128.8	73.8	44.1	34.2	27.0	23.0	15.7	13.0	6.79
1.70V	193.1	123.1	71.4	42.6	33.2	26.2	22.4	15.4	12.8	6.71
1.75V	179.7	117.7	68.7	41.1	32.2	25.6	21.8	15.2	12.7	6.62
1.80V	165.9	112.5	66.1	39.6	31.3	24.8	21.2	15.0	12.5	6.56
1.85V	137.7	96.9	59.3	36.3	28.9	23.1	19.8	14.0	11.8	6.23

Constant Power Discharge Characteristics : W/Cell (25°C)


F.V/Time	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	377.1	243.7	143.5	86.2	67.3	53.2	45.5	31.0	25.9	13.6
1.65V	365.8	236.4	139.4	83.9	65.5	52.0	44.4	30.7	25.6	13.4
1.70V	347.8	228.2	135.7	81.6	64.0	50.7	43.4	30.3	25.3	13.2
1.75V	328.3	220.4	131.5	79.1	62.4	49.6	42.5	29.9	25.0	13.1
1.80V	307.4	212.7	127.2	76.6	60.7	48.4	41.5	29.5	24.7	13.0
1.85V	258.7	185.0	114.8	70.6	56.4	45.1	38.9	27.7	23.3	12.3

(Note) The above characteristics data are average values obtained within three charge/discharge cycle not the minimum values. The battery must be fully charged before the capacity test. The C₁₀ should reach 95% after the first cycle and 100% after the third cycle.


FT12-125(12V125Ah)




Discharge Characteristics Curve




Charge Characteristic Curve For Standby Use(IU)




Cycle Life In Relation To Depth Of Discharge




Relationship Between Charging Voltage And Temperature




Temperature Effects On Capacity




Storage Characteristics



Effect Of Temperature On Long Term Life



Life Characteristics Of Standby Use



(Note) All above information shall be changed without prior notice, RITAR reserves the right to explain and update the latest information.