



HR12-800W(12V800W)

Specification

Cells Per Unit	6
Voltage Per Unit	12
Capacity	800W@15min-rate to 1.67V per cell @25°C
Weight	Approx. 72.0Kg (Tolerance±3.0%)
Internal Resistance	Approx. 2.6 mΩ
Terminal	F10(M8)
Max. Discharge Current	2400A (5 sec)
Short Circuit Current	4200A
Design Life	15 years
Max. Charging Current	72.0 A
Reference Capacity	C10 230.0AH C20 240.0AH
Standby Use Voltage	13.50 V~13.62 V @ 25°C Temperature Compensation: -3mV/°C/Cell
Equalization Voltage	14.10 V~14.40 V @ 25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -20°C~60°C Charge: 0°C~50°C Storage: -20°C~60°C
Normal Operating Temperature Range	25°C±5°C
Self Discharge	RITAR Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C and then recharging is recommended. Monthly Self-discharge ratio is less than 3% at 25°C. Please charge batteries before using.
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.



HR (High Rate) series Valve Regulated Lead Acid (VRLA) battery is designed for heavy load discharge applications with 15 years design life in float service. By using strong grids, thick plate and specially designed active material. It is with lower I.R, lower self discharge rate, high power, and longer service life. The HR series battery offers 30% more power output than the standard series. It is suitable for high power standby used, such as datacenter, UPS, EPS etc.



ISO 9001



ISO 14001




OHSAS 18001



MH 28539



Dimensions



Constant Current Discharge Characteristics : A (25°C)

F.V/Time	5MIN	8MIN	10MIN	15MIN	20MIN	30MIN	60MIN	90MIN
1.60V	783.4	655.1	579.8	442.4	360.2	265.5	153.6	110.3
1.67V	710.9	600.7	535.9	412.5	338.6	251.2	146.6	105.8
1.70V	680.6	577.5	516.6	400.0	329.1	245.2	143.7	103.7
1.75V	628.4	537.9	484.3	378.4	312.6	234.8	138.7	100.5
1.80V	575.8	498.1	452.0	358.0	297.9	224.9	133.7	97.2
1.85V	494.2	424.3	383.0	307.9	258.6	198.9	120.8	88.6

Constant Power Discharge Characteristics : WPC (25°C)


F.V/Time	5MIN	8MIN	10MIN	15MIN	20MIN	30MIN	60MIN	90MIN
1.60V	1439	1220	1091	843.2	692.3	515.9	288.6	208.7
1.67V	1340	1145	1029	800.0	660.7	494.7	277.7	201.7
1.70V	1296	1110	1000	781.4	646.5	484.7	273.2	198.9
1.75V	1216	1049	950.2	747.6	620.5	468.7	265.7	193.6
1.80V	1132	984.8	897.3	714.3	597.2	452.3	257.7	188.3
1.85V	985.8	850.6	770.4	620.9	523.2	403.4	234.4	173.2

(Note) The above characteristics data are average values obtained within three charge/discharge cycle not the minimum values.


HR12-800W(12V800W)




Discharge Characteristics Curve




Charge Characteristic Curve For Standby Use




Storage Characteristics




Relationship Between Charging Voltage And Temperature




Temperature Effects On Capacity




Relationship of OCV And State of Charge(20°C)



Effect Of Temperature On Long Term Life



Life Characteristics Of Standby Use



(Note) All above information shall be changed without prior notice, Ritar reserves the right to explain and update the latest information.

HENGYANG RITAR POWER CO.,LTD.
URL: www.ritarpower.com

Add: No.1 Huagong Road, Songmu Industrial Park, Shigu District, Hengyang, Hunan, China 421001
Tel: +86-734-8595528 Fax: +86-734-8595518 E-mail: sales@ritarpower.com

Version 22A-1-K