

PRODUCT DETAILS

PRODUCT CODE	MF95D31L		
WARRANTY	18 months (Commercial Use) *		
CHARACTERISTIC	Sealed Maintenance Free Lead Acid Battery		
GROUP SIZE	N70		
CASE AND LID	Material	:	Polypropylene (PP)
	Handle	:	1 pc Plastic
	Ledges	:	Front Ledge (FL)
	Venting System	:	Centralized system with Degassing vents on sides



DIMENSIONS, WEIGHT, AND LAYOUT

OVERALL DIMENSIONS	METRIC
LENGTH, mm	304
WIDTH, mm	174
CASE HEIGHT, mm	203
TOTAL HEIGHT, mm	224
APPROXIMATE WEIGHT, kg	22.65

TERMINAL DATA	METRIC
TYPE	SAE
TERMINAL HEIGHT, mm	18.5±1.5
BOTTOM DIAMETER, mm	Positive: 19.5+0/-0.3 Negative: 17.9+0/-0.3
TAPER	1:9
POLARITY	C (Positive Right)

CAPACITY SPECIFICATIONS

COLD CRANKING AMPS (CCA)	850 CCA
AMPERE-HOUR AT 20-HOUR CAPACITY	95 Ah
RESERVE CAPACITY (RC)	180 mins

MAX CHARGING VOLTAGE	14.8 V at 25°C
FLOAT CHARGING VOLTAGE	13.5 V – 13.8 V at 25°C
OPERATING TEMPERATURE	-40°C to 80°C Optimal Temperature: 25°C ± 5°C

