

PRODUCT DETAILS

PRODUCT CODE	MFD26EF		
CHARACTERISTIC	Lead Acid (Enhanced Flooded Battery)		
GROUP SIZE	D26		
	Material : Polypropylene (PP)		
	Handle : 1pc plastic		
	Ledge : Front Ledge (FL)	7	
CASE AND LID	Vent : Centralised venting on sides	STOP START STOP START EFB	
		24 Months Warranty*	

DIMENSIONAL SPECIFICATIONS


OVERALL DIMENSIONS	METRIC (mm)
LENGTH	258
WIDTH	172
HEIGHT (bottom to top cover)	200
TOTAL HEIGHT (bottom to top of terminal)	220
APPROXIMATE WEIGHT, kg	20.0

TERMINAL DATA	POSITIVE	NEGATIVE
TYPE	SAE	SAE
TERMINAL HEIGHT (mm)	18.5±1.50	18.5±1.50
BOTTOM DIAMETER (mm)	19.5+0/-0.3	19.5+0/-0.3
TAPER	1:9	1:9
POLARITY	C (Positive Right)	

CAPACITY SPECIFICATIONS

	700 CCA	
COLD CRANKING AMPS (CCA)	Test reference: AS60095:2022 Rated CCA DCH at 18°C for 30 sec	
AMPERE-HOUR AT	75 Ah	
20-HOUR CAPACITY	Test reference: AS60095:2022 Rated AH DCH at 10.5 V cut-off voltage	

DECEDATE.	130 min
RESERVE CAPACITY TEST	Test reference: AS60095:2022 25Amps DCH at 10.5V cut-off voltage



^{*}Warranty terms and conditions apply

Revision No. 00