

PRODUCT DETAILS

PRODUCT CODE	MFN200R	
WARRANTY	24 months (Commercial Use) *	
CHARACTERISTIC	Sealed Maintenance Free Lead Acid Battery	
GROUP SIZE	H52	
	Material : Polypropylene (PP)	
CASE AND LID	Handle : 2 pc Rope	
CASE AND EID	Ledges : Front No (NL)	
	Venting Centralized system with	
	System Degassing vents on sides	



DIMENSIONS, WEIGHT, AND LAYOUT


, , , , , , , , , , , , , , , , , , ,		
OVERALL DIMENSIONS	METRIC	
LENGTH, mm	524	
WIDTH, mm	278	
CASE HEIGHT, mm	225	
TOTAL HEIGHT, mm	251	
APPROXIMATE WEIGHT, kg	53.17	

TERMINAL DATA	METRIC
ТҮРЕ	SAE
TERMINAL HEIGHT, mm	18.5±1.5
BOTTOM DIAMETER, mm	Positive: 19.5+0/-0.3 Negative: 17.9+0/-0.3
TAPER	1:9
POLARITY	E (Positive Right)


CAPACITY SPECIFICATIONS


<u> </u>		
COLD CRANKING AMPS (CCA)	1250 CCA	
AMPERE-HOUR AT 20-HOUR CAPACITY	200 Ah	
RESERVE CAPACITY (RC)	408 mins	

MAX CHARGING VOLTAGE	14.8 V at 25°C
FLOAT CHARGING VOLTAGE	13.5 V – 13.8 V at 25°C
OPERATING TEMPERATURE	-40°C to 80°C** Optimal Temperature: $25^{\circ}\text{C} \pm 5^{\circ}\text{C}$









 $^{{}^{*}}$ Warranty terms and conditions apply.

^{**}Based on normal engine bay temperature.