

PRODUCT DETAILS

| | | |
|-----------------------|---|--|
| PRODUCT CODE | MFU1R | |
| WARRANTY | 18 months (Private/Commercial Use) * | |
| CHARACTERISTIC | Sealed Maintenance Free Lead Acid Battery | |
| GROUP SIZE | GU1 | |
| CASE AND LID | Material : Polypropylene (PP) | |
| | Handle : 1 pc Plastic | |
| | Ledges : No Ledge (NL) | |
| | Venting System : Centralized system with Degassing vents on sides | |
| | | |

DIMENSIONS, WEIGHT, AND LAYOUT


| OVERALL DIMENSIONS | METRIC |
|------------------------|--------|
| LENGTH, mm | 196 |
| WIDTH, mm | 128 |
| CASE HEIGHT, mm | 159 |
| TOTAL HEIGHT, mm | 184 |
| APPROXIMATE WEIGHT, kg | 8.95 |

| TERMINAL DATA | METRIC |
|---------------------|--------------------|
| TYPE | U1 |
| TERMINAL HEIGHT, mm | 23.5 |
| BOTTOM DIAMETER, mm | - |
| TAPER | - |
| POLARITY | C (Positive Right) |

CAPACITY SPECIFICATIONS

| | |
|---------------------------------|---------|
| COLD CRANKING AMPS (CCA) | 350 CCA |
| AMPERE-HOUR AT 20-HOUR CAPACITY | 35 Ah |
| RESERVE CAPACITY (RC) | 45 mins |

| | |
|------------------------|--|
| MAX CHARGING VOLTAGE | 14.8 V at 25°C |
| FLOAT CHARGING VOLTAGE | 13.5 V – 13.8 V at 25°C |
| OPERATING TEMPERATURE | -40°C to 80°C** Optimal Temperature: 25°C ± 5°C |



*Warranty terms and conditions apply.

**Based on normal engine bay temperature.

(Note) The company reserves the right to update the information above without prior notice.