

PRODUCT DETAILS

| PRODUCT CODE | MFULD23L | | |
|----------------|---|---|--------------------------|
| WARRANTY | 60 months (Private Passenger Use) * | | |
| CHARACTERISTIC | Accessible Maintenance Free Lead Acid Battery | | |
| GROUP SIZE | NS50 | | |
| | Material | : | Polypropylene (PP) |
| CASE AND LID | Handle | : | 1 pc Plastic |
| CASE AND LID | Ledges | : | Front Ledge (FL) |
| | Venting | | Centralized system with |
| | System | • | Degassing vents on sides |



DIMENSIONS, WEIGHT, AND LAYOUT


| OVERALL DIMENSIONS | METRIC |
|------------------------|--------|
| LENGTH, mm | 233 |
| WIDTH, mm | 173 |
| CASE HEIGHT, mm | 201 |
| TOTAL HEIGHT, mm | 222 |
| APPROXIMATE WEIGHT, kg | 16.09 |


| TERMINAL DATA | METRIC |
|---------------------|--|
| ТҮРЕ | SAE |
| TERMINAL HEIGHT, mm | 18.5±1.5 |
| BOTTOM DIAMETER, mm | Positive: 19.5+0/-0.3 Negative: 17.9+0/-0.3 |
| TAPER | 1:9 |
| POLARITY | C (Positive Right) |


CAPACITY SPECIFICATIONS


| COLD CRANKING AMPS (CCA) | 650 CCA | |
|------------------------------------|----------|--|
| AMPERE-HOUR AT 20-HOUR CAPACITY | 75 Ah | |
| RESERVE CAPACITY (RC) | 120 mins | |

| MAX CHARGING VOLTAGE | 14.8 V at 25°C |
|---------------------------|--|
| FLOAT CHARGING VOLTAGE | 13.5 V – 13.8 V at 25°C |
| OPERATING TEMPERATURE | -40°C to 80°C** Optimal Temperature: 25°C ± 5°C |









^{*}Warranty upon registration /Warranty terms and conditions apply. **Based on normal engine bay temperature.