

## **PRODUCT DETAILS**

PRODUCT CODE	MRV70	
WARRANTY	24 months (Private/Commercial Use) *	
CHARACTERISTIC	Accessible Maintenance Free Lead Acid Battery	
GROUP SIZE	N70	
	Material : Polypropylene (PP)	
CASE AND LID	Handle : 1 pc Plastic	
CASE AND LID	Ledges : Front Ledge (FL)	
	Venting Centralized system with System Degassing vents on sides	



## **DIMENSIONS, WEIGHT, AND LAYOUT**

,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
OVERALL DIMENSIONS	METRIC
LENGTH, mm	304
WIDTH, mm	173
CASE HEIGHT, mm	203
TOTAL HEIGHT, mm	223
APPROXIMATE WEIGHT, kg	25.98

TERMINAL DATA	METRIC
TYPE	Dual Marine
TERMINAL HEIGHT, mm	18.5±1.5
BOTTOM DIAMETER, mm	Positive: 19.5+0/-0.3 Negative: 17.9+0/-0.3
TAPER	1:9
POLARITY	D (Positive Left)


## **CAPACITY SPECIFICATIONS**


COLD CRANKING AMPS (CCA)	760 CCA
AMPERE-HOUR AT 20-HOUR CAPACITY	105 Ah
RESERVE CAPACITY (RC)	160 mins


MAX CHARGING VOLTAGE	14.8 V at 25°C	
FLOAT CHARGING		
VOLTAGE	13.5 V – 13.8 V at 25°C	
OPERATING TEMPERATURE	-40°C to 80°C**	
	Optimal Temperature: 25°C + 5°C	


<sup>\*</sup>Warranty terms and conditions apply.
\*\*Based on normal engine bay temperature.











<sup>\*</sup>Warranty terms and conditions apply.
\*\*Based on normal engine bay temperature.