

PRODUCT DETAILS

PRODUCT CODE	N55D23R		
WARRANTY	30 months (Private Passenger Use) *		
CHARACTERISTIC	Sealed Maintenance Free Lead Acid Battery		
GROUP SIZE	NS60		
CASE AND LID	Material	: Pc	olypropylene (PP)
	Handle	: 1	pc Plastic
	Ledges	: No	c Ledge (NL)
	Venting	. Ce	entralized system with
	System	. De	egassing vents on sides



DIMENSIONS, WEIGHT, AND LAYOUT


OVERALL DIMENSIONS	METRIC
LENGTH, mm	233
WIDTH, mm	173
CASE HEIGHT, mm	201
TOTAL HEIGHT, mm	222
APPROXIMATE WEIGHT, kg	15.18


TERMINAL DATA	METRIC
ТҮРЕ	SAE
TERMINAL HEIGHT, mm	18.5±1.5
BOTTOM DIAMETER, mm	Positive: 19.5+0/-0.3 Negative: 17.9+0/-0.3
TAPER	1:9
POLARITY	D (Positive Left)

CAPACITY SPECIFICATIONS

2 / 10.1 / 0.1 _ 0.1 0.		
COLD CRANKING AMPS (CCA)	560 CCA	
AMPERE-HOUR AT 20-HOUR CAPACITY	60 Ah	
RESERVE CAPACITY (RC)	85 mins	

MAX CHARGING VOLTAGE	14.8 V at 25°C	
FLOAT CHARGING VOLTAGE	13.5 V – 13.8 V at 25°C	
OPERATING TEMPERATURE	-40°C to 80° C** Optimal Temperature: 25° C \pm 5° C	





172.00

^{*}Warranty terms and conditions apply.
**Based on normal engine bay temperature.