

PRODUCT DETAILS

PRODUCT CODE	N70ZZ	X
WARRANTY	30 months (F	Private Passenger Use) *
CHARACTERISTIC	Sealed Maint	tenance Free Lead Acid Battery
GROUP SIZE	N70	
CASE AND LID	Material	: Polypropylene (PP)
	Handle	: 1 pc Plastic
	Ledges	: Front Ledge (FL)
	Venting	. Centralized system with
	System	Degassing vents on sides



DIMENSIONS, WEIGHT, AND LAYOUT


OVERALL DIMENSIONS	METRIC
LENGTH, mm	304
WIDTH, mm	173
CASE HEIGHT, mm	203
TOTAL HEIGHT, mm	223
APPROXIMATE WEIGHT, kg	19.4


TERMINAL DATA	METRIC
TYPE	SAE
TERMINAL HEIGHT, mm	18.5±1.5
BOTTOM DIAMETER, mm	Positive: 19.5+0/-0.3 Negative: 17.9+0/-0.3
TAPER	1:9
POLARITY	C (Positive Right)


CAPACITY SPECIFICATIONS

# 11 7 10 11 1 0 1 1 1 1 1 1 1 1 1 1 1 1	
COLD CRANKING AMPS (CCA)	680 CCA
AMPERE-HOUR AT 20-HOUR CAPACITY	75 Ah
RESERVE CAPACITY (RC)	130 mins

MAX CHARGING VOLTAGE	14.8 V at 25°C
FLOAT CHARGING VOLTAGE	13.5 V – 13.8 V at 25°C
OPERATING TEMPERATURE	-40°C to 80° C** Optimal Temperature: 25° C $\pm 5^{\circ}$ C







^{*}Warranty terms and conditions apply.
**Based on normal engine bay temperature.