

PRODUCT DETAILS

| PRODUCT CODE | N88 | | |
|----------------|---|---|-------------------------------|
| WARRANTY | 30 months (Private Passenger Use) * | | |
| CHARACTERISTIC | Sealed Maintenance Free Lead Acid Battery | | |
| GROUP SIZE | LN5 | | |
| | Material | : | Polypropylene (PP) |
| j | Handle | : | 2 pc Plastic |
| CASE AND LID | Ledges | : | End and Front Ledge (EL & FL) |
| | Venting | | Centralized system with |
| | System | • | Degassing vents on sides |



DIMENSIONS, WEIGHT, AND LAYOUT


| OVERALL DIMENSIONS | METRIC |
|------------------------|--------|
| LENGTH, mm | 345 |
| WIDTH, mm | 175 |
| CASE HEIGHT, mm | 153 |
| TOTAL HEIGHT, mm | 175 |
| APPROXIMATE WEIGHT, kg | 20.2 |


| TERMINAL DATA | METRIC |
|---------------------|--|
| ТҮРЕ | SAE |
| TERMINAL HEIGHT, mm | 18.5±1.5 |
| BOTTOM DIAMETER, mm | Positive: 19.5+0/-0.3 Negative: 17.9+0/-0.3 |
| TAPER | 1:9 |
| POLARITY | C (Positive Right) |


CAPACITY SPECIFICATIONS


| COLD CRANKING AMPS (CCA) | 780 CCA |
|---------------------------------|----------|
| AMPERE-HOUR AT 20-HOUR CAPACITY | 80 Ah |
| RESERVE CAPACITY (RC) | 140 mins |

| MAX CHARGING VOLTAGE | 14.8 V at 25°C |
|---------------------------|--|
| FLOAT CHARGING VOLTAGE | 13.5 V – 13.8 V at 25°C |
| OPERATING TEMPERATURE | -40°C to 80° C** Optimal Temperature: 25° C \pm 5° C |









 $^{{}^{*}}$ Warranty terms and conditions apply.

^{**}Based on normal engine bay temperature.