

PRODUCT DETAILS

PRODUCT CODE	NS50PL		
WARRANTY	30 months (Private Passenger Use) *		
CHARACTERISTIC	Sealed Maintenance Free Lead Acid Battery		
GROUP SIZE	A46		
	Material	:	Polypropylene (PP)
	Handle	:	1 pc Plastic
CASE AND LID	Ledges	:	End and Front Ledge (FL & EL)
	Venting		Centralized system with
	System	•	Degassing vents on sides



DIMENSIONS, WEIGHT, AND LAYOUT


OVERALL DIMENSIONS	METRIC
LENGTH, mm	228
WIDTH, mm	171
CASE HEIGHT, mm	182
TOTAL HEIGHT, mm	208
APPROXIMATE WEIGHT, kg	13.99

TERMINAL DATA	METRIC
TYPE	DFP
TERMINAL HEIGHT, mm	24.0±0.2
BOTTOM DIAMETER, mm	Positive: 20.1+0/-0.2 Negative: 18.5+0/-0.2
TAPER	1:9
POLARITY	C (Positive Right)


CAPACITY SPECIFICATIONS


COLD CRANKING AMPS (CCA)	480 CCA
AMPERE-HOUR AT 20-HOUR CAPACITY	40 Ah
RESERVE CAPACITY (RC)	75 mins

MAX CHARGING VOLTAGE	14.8 V at 25°C
FLOAT CHARGING VOLTAGE	13.5 V – 13.8 V at 25°C
OPERATING TEMPERATURE	-40°C to 80° C** Optimal Temperature: 25° C \pm 5° C



236.63





 $^{{}^{*}}$ Warranty terms and conditions apply.

^{**}Based on normal engine bay temperature.