

# ★ **SUPERCHARGE**<sup>®</sup>

## **BATTERIES**



# CLASSIC



**Best in class original equipment battery replacement.**

- Fully-sealed Maintenance-Free battery
- Built with Lead-Calcium Tropicalised\* Plates
- Assembled using hardened alloys and intercell connections
- Formulated with high purity lead and electrolyte

**Reliable, Long service life, Longest warranty.**

\* Design which aids in heat dissipation inside the battery, thereby reducing life degradation due to extreme heat of under-bonnet conditions.

[supercharge.com.au](http://supercharge.com.au) | 1300737244

## CLASSIC RANGE

TYPE	NOMINAL VOLTAGE V	CCA (SAE)	RC (min)	AH (20HR)	OVERALL DIMENSION (mm)			WET WEIGHT (kg)	ASSEMBLY	POST TYPE	BASE WARRANTY (Private Use)	EXTENDED WARRANTY (Private Use)	COMMERCIAL USE WARRANTY
					L	W	TH						
<b>POPULAR AUTOMOTIVE</b>													
NS50P	12	480	75	40	237	171	203	13.60	D	STD	30	-	12
NS50PL	12	480	75	40	237	171	208	13.99	C	DFP	30	-	12
<b>JAPANESE AUTOMOTIVE</b>													
NS40ZL	12	340	55	38	196	128	219	9.16	C	PT	30	-	12
NS40ZAL	12	340	55	38	196	128	219	9.16	C	STD	30	-	12
NS40ZA	12	340	55	38	196	128	219	9.16	C	STD	30	-	12
NS40ZFL	12	340	55	38	187	136	220	9.16	C	PT	30	-	12
NS40Z	12	340	55	38	196	128	219	9.16	D	PT	30	-	12
NS60R	12	450	75	48	234	127	220	12.96	D	PT	30	-	12
NS60L	12	450	75	48	234	127	220	12.96	C	PT	30	-	12
NS60RS	12	450	75	48	236	128	219	12.96	D	STD	30	-	12
NS60LS	12	450	75	48	236	128	219	12.96	C	STD	30	-	12
N55D23R	12	560	85	60	233	173	222	16.46	D	STD	30	-	12
N55D23L	12	560	85	60	233	173	222	16.46	C	STD	30	-	12
<b>EUROPEAN AUTOMOTIVE</b>													
N55	12	500	90	54	242	175	175	12.26	C	STD	30	-	12
N55R	12	500	90	54	242	175	175	12.67	D	STD	30	-	12
N55H	12	600	90	60	242	175	190	13.75	C	STD	30	-	12
N66	12	650	110	70	277	175	175	15.76	C	STD	30	-	12
N66R	12	650	110	70	277	175	175	16.73	D	STD	30	-	12
N66H	12	700	130	74	277	175	190	18.72	C	STD	30	-	12
N66HR	12	700	130	74	277	175	190	18.72	D	STD	30	-	12
N77	12	750	140	75	315	175	175	18.70	C	STD	30	-	12
N77H	12	750	160	90	315	175	190	19.85	C	STD	30	-	12
N88	12	780	140	80	351	175	175	22.14	C	STD	30	-	12
N88H	12	870	180	100	351	175	190	21.97	C	STD	30	-	12
<b>4WD AND TRUCK APPLICATIONS</b>													
NS70	12	615	95	70	259	173	223	19.29	D	STD	30	-	12
NS70L	12	615	95	70	259	173	223	19.29	C	STD	30	-	12
N70ZZX	12	680	130	75	304	173	224	22.65	D	STD	30	-	12
N70ZZLX	12	680	130	75	304	173	224	22.65	C	STD	30	-	12

### AUSTRALIA

#### NEW SOUTH WALES

31-39 Sturt Street, Smithfield NSW 2164

Sydney 02 9840 2828

#### QUEENSLAND

a1 1/14 Dixon Street, Yatala QLD 4207

Yatala 07 3711 8900

#### VICTORIA & TASMANIA

93 Cherry Lane, Laverton North VIC 3026

Melbourne 03 9267 8400

#### NEW ZEALAND

#### AUCKLAND

72B Highbrook Drive East Tamaki

Auckland 09 9758900

#### SOUTH AUSTRALIA & NORTHERN TERRITORY

9 Johansson Road, Wingfield SA 5013

Wingfield 08 8193 6800

#### WESTERN AUSTRALIA

14 Aitken Way, Kewdale WA 6105

Kewdale 08 9259 9200

**1300 737 244**

[www.supercharge.com.au](http://www.supercharge.com.au)

**0800 188 122**

[www.superchargebatteries.co.nz](http://www.superchargebatteries.co.nz)

