

★ SUPERCHARGE[®] **BATTERIES**



GOLDPLUS



**Designed to exceed original
equipment requirement.**

Best Performance, Longer Life.

- Built with More Lead-Calcium Tropicalised* Power Plates
- Formulated for high state of charge retention
- Advanced dense and compact battery construction
- Assembled using hardened alloys and intercell connections
- Fully-sealed Maintenance-Free battery
- High efficiency electrical flow design
- Formulated with high purity lead and electrolyte

Reliable, Long service life, Longest warranty.

* Design which aids in heat dissipation inside the battery, thereby reducing life degradation due to extreme heat of under-bonnet conditions.

supercharge.com.au | 1300737244

GOLDPLUS RANGE

TYPE	NOMINAL VOLTAGE V	CCA (SAE)	RC (min)	AH (20HR)	OVERALL DIMENSION (mm)			WET WEIGHT (kg)	ASSEMBLY	POST TYPE	BASE WARRANTY (Private Use)	EXTENDED WARRANTY (Private Use)	COMMERCIAL USE WARRANTY
					L	W	TH						
POPULAR AUTOMOTIVE													
MF43	12	410	60	46	238	138	212	12.00	H	DFP	40	50	18
MF50	12	650	107	60	237	171	203	15.71	D	STD	40	50	18
MF51	12	650	107	60	237	171	208	16.08	C	DFA	40	50	18
MF52	12	650	107	60	237	171	208	16.08	C	DFP	40	50	18
MF53	12	650	107	60	228	171	203	15.71	C	STD	40	50	18
JAPANESE AUTOMOTIVE													
MF40B20FL	12	370	-	40	187	136	220	9.30	C	PT	40	50	18
MF40B20	12	400	68	45	196	128	219	9.16	D	PT	40	50	18
MF40B20L	12	400	68	45	196	128	219	9.16	C	PT	40	50	18
MF40B20ZA	12	400	68	45	196	128	219	9.24	D	STD	40	50	18
MF40B20ZAL	12	400	68	45	196	128	219	9.24	C	STD	40	50	18
MF50D20L	12	460	80	50	200	174	221	13.79	C	STD	40	50	18
MF55B24R	12	500	90	56	236	128	219	12.96	D	PT	40	50	18
MF55B24L	12	500	90	56	236	128	219	12.96	C	PT	40	50	18
MF55B24RS	12	500	90	56	236	128	219	13.05	D	STD	40	50	18
MF55B24LS	12	500	90	56	236	128	219	13.05	C	STD	40	50	18
MF75D23R	12	650	120	75	233	173	222	17.07	D	STD	40	50	18
MF75D23L	12	650	120	75	233	173	222	17.07	C	STD	40	50	18
EUROPEAN AUTOMOTIVE													
MF44	12	510	70	50	208	175	175	12.26	C	STD	40	50	18
MF44H	12	420	72	45	208	174	190	12.67	C	STD	40	50	18
MF55	12	640	105	62	242	175	175	13.75	C	STD	40	50	18
MF55R	12	640	105	62	242	175	175	13.75	D	STD	40	50	18
MF55H	12	680	125	75	242	175	190	14.89	C	STD	40	50	18
MF66	12	760	130	80	277	175	175	16.73	C	STD	40	50	18
MF66R	12	760	130	80	277	175	175	16.73	D	STD	40	50	18
MF66H	12	800	165	90	277	175	190	18.72	C	STD	40	50	18
MF66HR	12	800	165	90	277	175	190	18.72	D	STD	40	50	18
MF77	12	840	165	90	315	175	175	18.70	C	STD	40	-	18
MF77H	12	840	175	95	315	175	190	19.85	C	STD	40	-	18
MF77HRX	12	915	165	110	315	175	190	21.32	D	STD	40	-	18
MF88	12	850	160	90	351	175	175	22.14	C	STD	40	-	18
MF88H	12	950	210	110	351	175	190	21.97	C	STD	40	-	18
US AUTOMOTIVE													
MF58	12	540	90	50	254	182	178	13.30	D	STD	40	-	18
MF58R	12	540	90	50	254	182	178	13.30	C	STD	40	-	18
MF65	12	780	140	80	286	189	192	19.13	D	STD	40	-	18
MF78	12	760	120	70	260	179	180	17.52	D	ST	40	-	18
MF78-DT	12	760	120	70	260	179	200	17.83	D	DT	40	-	18
4WD/SUV/TRUCK AND INDUSTRIAL APPLICATION													
MF80D26R	12	750	150	85	259	174	223	19.29	D	STD	40	-	18
MF80D26L	12	750	150	85	259	174	223	19.29	C	STD	40	-	18
MF95D31R	12	850	180	95	304	174	224	22.65	D	STD	40	-	18
MF95D31L	12	850	180	95	304	174	224	22.65	C	STD	40	-	18
MF31-931	12	1000	210	110	330	172	237	26.51	H	STD	-	-	24
MF31-930	12	1000	210	110	330	172	237	26.43	H	TS	-	-	24
MFN94	12	900	275	145	508	208	204	36.61	D	STD	-	-	24
MFN100	12	815	200	100	405	173	231	26.59	D	STD	-	-	24
MFN100L	12	815	200	100	405	173	231	26.59	C	STD	-	-	24
MFN120R	12	900	300	150	505	180	233	36.43	F	STD	-	-	24
MFN120L	12	900	300	150	505	180	233	36.43	E	STD	-	-	24
MFN150R	12	1000	330	165	508	220	236	42.32	F	STD	-	-	24
MFN150L	12	1000	330	165	508	220	236	42.32	E	STD	-	-	24
MFN200R	12	1250	408	200	524	278	251	53.08	F	STD	-	-	24
MFN200L	12	1250	408	200	524	278	251	53.08	E	STD	-	-	24
NI20LX	12	1150	300	154	513	188	224	-	E	STD	-	-	24
EUROPEAN TRUCK													
DIN100L	12	950	-	110	394	174	190	28.30	C	STD	-	-	24
EMFN120R	12	930	200	120	514	189	217	33.70	F	STD	-	-	24
EMFN120L	12	930	200	120	514	189	217	33.70	E	STD	-	-	24
EMFN150RL	12	1030	350	180	511	222	217	45.00	F	STD	-	-	24
EMFN150R	12	1030	300	150	514	223	217	39.40	F	STD	-	-	24
EMFN150L	12	1030	300	150	514	223	217	39.40	E	STD	-	-	24
EMFN200R	12	1150	400	200	518	272	237	53.20	F	STD	-	-	24
EMFN200L	12	1150	400	200	518	272	237	53.20	E	STD	-	-	24

ABBREVIATIONS & BATTERY ASSEMBLIES

DFA	Dual Fit Aligned Terminals	ST	Side Terminal
DFP	Dual Fit Parallel Terminals	STD	Standard Terminal
DST	Dual System Terminals	TS	Top Stud Terminal
PT	Pencil Terminal		

