

PRODUCT DETAILS

PRODUCT CODE	SMF55D23L		
WARRANTY	40 months (Private Passenger Use) *		
CHARACTERISTIC	Sealed Maintenance Free Lead Acid Battery		
GROUP SIZE	NS50		
CASE AND LID	Material	:	Polypropylene (PP)
	Handle	:	1 pc Plastic
	Ledges	:	No Ledge (NL)
	Venting		Centralized system with
	System	•	Degassing vents on sides



DIMENSIONS, WEIGHT, AND LAYOUT


OVERALL DIMENSIONS	METRIC
LENGTH, mm	233
WIDTH, mm	173
CASE HEIGHT, mm	201
TOTAL HEIGHT, mm	222
APPROXIMATE WEIGHT, kg	17.04


TERMINAL DATA	METRIC
ТҮРЕ	SAE
TERMINAL HEIGHT, mm	18.5±1.5
BOTTOM DIAMETER, mm	Positive: 19.5+0/-0.3 Negative: 17.9+0/-0.3
TAPER	1:9
POLARITY	C (Positive Right)

CAPACITY SPECIFICATIONS


COLD CRANKING AMPS (CCA)	615 CCA	
AMPERE-HOUR AT 20-HOUR CAPACITY	70 Ah	
RESERVE CAPACITY (RC)	115 mins	

MAX CHARGING VOLTAGE	14.8 V at 25°C
FLOAT CHARGING VOLTAGE	13.5 V – 13.8 V at 25°C
OPERATING TEMPERATURE	-40°C to 80°C** Optimal Temperature: 25°C ± 5°C









^{*}Warranty upon registration /Warranty terms and conditions apply. **Based on normal engine bay temperature.