

PRODUCT DETAILS

PRODUCT CODE	SMF66I	Н
WARRANTY	40 months (Private Passenger Use) *	
CHARACTERISTIC	Sealed Maintenance Free Lead Acid Battery	
GROUP SIZE	LN3	
CASE AND LID	Material	: Polypropylene (PP)
	Handle	: 2 pc Plastic
	Ledges	End and Front Ledge (EL & : FL)
	Venting	. Centralized system with
	System	· Degassing vents on sides



DIMENSIONS, WEIGHT, AND LAYOUT


OVERALL DIMENSIONS	METRIC
LENGTH, mm	271
WIDTH, mm	175
CASE HEIGHT, mm	168
TOTAL HEIGHT, mm	190
APPROXIMATE WEIGHT, kg	17.72


TERMINAL DATA	METRIC
TYPE	SAE
TERMINAL HEIGHT, mm	18.5±1.5
BOTTOM DIAMETER, mm	Positive: 19.5+0/-0.3 Negative: 17.9+0/-0.3
TAPER	1:9
POLARITY	C (Positive Right)


CAPACITY SPECIFICATIONS


COLD CRANKING AMPS (CCA)	780 CCA
AMPERE-HOUR AT 20-HOUR CAPACITY	85 Ah
RESERVE CAPACITY (RC)	160 mins

MAX CHARGING VOLTAGE	14.8 V at 25°C
FLOAT CHARGING VOLTAGE	13.5 V – 13.8 V at 25°C
OPERATING TEMPERATURE	-40°C to 80°C** Optimal Temperature: 25°C ± 5°C









 $[\]hbox{*Warranty upon registration /Warranty terms and conditions apply.}$

^{**}Based on normal engine bay temperature.