

PRODUCT DETAILS

PRODUCT CODE	SMF86ZT
WARRANTY	18 months (Commercial Use) *
CHARACTERISTIC	Accessible Maintenance Free Lead Acid Battery
GROUP SIZE	G31
	Material : Polypropylene (PP)
CASE AND LID	Handle : 2 pc Plastic
	Ledges : No Ledge (NL)
	Venting Centralized system with
	System Degassing vents on sides



DIMENSIONS, WEIGHT, AND LAYOUT


OVERALL DIMENSIONS	METRIC
LENGTH, mm	329
WIDTH, mm	172
CASE HEIGHT, mm	215
TOTAL HEIGHT, mm	236
APPROXIMATE WEIGHT, kg	24.42

TERMINAL DATA	METRIC
TYPE	Threaded
TERMINAL HEIGHT, mm	16
BOTTOM DIAMETER, mm	-
TAPER	-
POLARITY	H (Positive Left)


CAPACITY SPECIFICATIONS

COLD CRANKING AMPS (CCA)	950 CCA
AMPERE-HOUR AT 20-HOUR CAPACITY	110 Ah
RESERVE CAPACITY (RC)	200 mins

MAX CHARGING VOLTAGE	14.8 V at 25°C
FLOAT CHARGING VOLTAGE	13.5 V – 13.8 V at 25°C
OPERATING TEMPERATURE	-40°C to 80°C** Optimal Temperature: 25°C ± 5°C









^{*}Warranty terms and conditions apply.
**Based on normal engine bay temperature.