

PRODUCT DETAILS

PRODUCT CODE	SMFU1R
WARRANTY	12 months (Private/Commercial Use) *
CHARACTERISTIC	Sealed Maintenance Free Lead Acid Battery
GROUP SIZE	GU1
CASE AND LID	Material : Polypropylene (PP)
	Handle : 1 pc Plastic
	Ledges : No Ledge (NL)
	Venting System : Centralized system with Degassing vents on sides



DIMENSIONS, WEIGHT, AND LAYOUT


OVERALL DIMENSIONS	METRIC
LENGTH, mm	196
WIDTH, mm	128
CASE HEIGHT, mm	159
TOTAL HEIGHT, mm	184
APPROXIMATE WEIGHT, kg	7.72

TERMINAL DATA	METRIC
TYPE	U1
TERMINAL HEIGHT, mm	23.5
BOTTOM DIAMETER, mm	-
TAPER	-
POLARITY	C (Positive Right)

CAPACITY SPECIFICATIONS

COLD CRANKING AMPS (CCA)	260 CCA
AMPERE-HOUR AT 20-HOUR CAPACITY	27 Ah
RESERVE CAPACITY (RC)	33 mins

MAX CHARGING VOLTAGE	14.8 V at 25°C
FLOAT CHARGING VOLTAGE	13.5 V – 13.8 V at 25°C
OPERATING TEMPERATURE	-40°C to 80°C** Optimal Temperature: 25°C ± 5°C



*Warranty terms and conditions apply.

**Based on normal engine bay temperature.

(Note) The company reserves the right to update the information above without prior notice.