

SUPER CHARGE

TECHNOLOGIES

MODEL: SPB1500 Power Pack



2 YEARS WARRANTY

Specifications

Cell	Cell Type	Cylindrical
	Cell Construction	LiFePO4
	Internal Battery Voltage	25.6v
	Internal Battery Capacity	60Ah-1536Wh
Input	Input Voltage	DC 12-30V
		110V(AC) - 90-120V
		220V(AC) - 200-240V
		Solar DC - 12 max (500w)
Charging	By Car Adaptor	12-30V/10amp (DC5521)
	By 12V Pin Plug	12-30V/500w (XT60)
	AC Charging	90-240V/50hz max 800w
Outlets	4 x USB - A	5V3A/9V2A/12V1.5A
	2 x USB - C	5V/9V/12V/15V/20V,5A
	1DC5521	13.6/3A
	Car Socket	13.6V/10A
AC OUTLETS	4 X AC Outlets	240v-50Hz
	Peak Power Cont	1600W
	Peak Power 5 Sec	1600W-1800W
	Peak Power 1 Sec	3000W
	Peak Power 0.5 Sec	3000W
	Output Wave	Pure Sine Wave
	Certification	AS/NZS 62368.1
	Operating Temp	0 - 45 °C
	Storage Temp	-10 to 45 °C
Stand By Time	Recharge every 3 months	

AUSTRALIA

1300 737 244

www.supercharge.com.au

NEW ZEALAND

0800 188 122

www.superchargebatteries.co.nz