



LITHIUM

CERTIFICATIONS
 UL1642 (Cell), CE (Pack), IEC62133 (Cell), UN38.3 (Cell / Pack), IEC62619 (Cell), ROHS (Cell)



ATLS12-130

Specifications

Electrical Specifications	Nominal Voltage	12.8V	
	Nominal Capacity	130 Ah	
	Nominal Power	1664 Wh	
	Parallel Connection	max 6 units	
	Series Connection	max 4 units	
	Circuit Protection	Overcharge, Over Discharge, Short Circuit, High Temperature, Cell Imbalance	
	Cycle life	"3000 cycles @100% DOD, 6000 cycles @80%DOD"	
Charge Specifications	Charge Profile	CC @ 0.2C to 14.4V, then CV @ 14.4V until current $\leq 0.01C$ (CC/CV)	
	Max Charge Voltage	14.4 \pm 0.2V	
	Charge Current	$\leq 65A$ (0.2C @ 26A)	
	Max Current	65A	
Discharge Specifications	Recommended Discharge Current	$\leq 65A$ (0.2C @ 26A)	
	Max Continuous Current	130A	
	Cut-off Voltage	10V	
Environmental Specifications	Charge Temperature	0°C to 55°C	60 \pm 25% Relative Humidity
	Discharge Temperature	-20°C to 60°C	
	Storage Temperature	-5°C to 45°C	
Mechanical Specifications	Dimensions, mm	330x173x216 (Group 31)	
	Approx Weight, kg	15	
	Terminal type	M8	
	Case Material	Plastic ABS	
	IP Rating	IP65	
	Cell Type	Cylindrical LiFePO4	

Circuit Protection	Characteristic	Parameters
Overcharge protection Cells	High voltage protection	3.75V \pm 0.05V
	Recovery point	3.55V \pm 0.05V
	Reset trigger	below reset value
	Time delay	5s
Over discharge protection Cells	Low voltage protection	2.2V \pm 0.05V
	Reset trigger	2.7V \pm 0.05V
	Reset trigger	Cut Load, Auto release
	Time delay	5s
Overcurrent	Max discharge current protection	700A \pm 50A
	Discharge current protection reset	Cut Load, Auto release
	Time delay	300mS

Circuit Protection	Characteristic	Parameters
Short circuit protection	Short circuit protection	1200A
	Time delay	$\leq 800\mu s$
High temperature protection	Max charge temperature	65°C \pm 3°C
	Recovery point	45°C \pm 3°C
	Time delay	10s
	Max discharge temperature	65°C \pm 3°C
	Recovery point	45°C \pm 3°C
	Time delay	10s
Cell imbalance protection	MOSFET over temperature protection	90°C \pm 5°C
	Vcell balancing condition	$\geq 3.6V$
	Vcell balancing condition	25-50mV
	Balancing current	116 \pm 10mA



LITHIUM

ATLS12-130

CERTIFICATIONS
 UL1642 (Cell), CE (Pack), IEC62133 (Cell), UN38.3 (Cell / Pack), IEC62619 (Cell), ROHS (Cell)



3 YEARS WARRANTY

Characteristics Curve

