

**PRODUCT DETAILS**

<b>PRODUCT CODE</b>	<b>D12</b>
<b>WARRANTY</b>	12 months (Private/Commercial Use) *
<b>CHARACTERISTIC</b>	Accessible Deep Cycle Lead Acid Battery
<b>GROUP SIZE</b>	D12
<b>CASE AND LID</b>	Material : Polypropylene (PP)
	Handle : No handle
	Ledges : No Ledge (NL)
	Venting System : Integrated with the caps



**DIMENSIONS, WEIGHT, AND LAYOUT**

OVERALL DIMENSIONS	METRIC
LENGTH, mm	229
WIDTH, mm	175
CASE HEIGHT, mm	186
TOTAL HEIGHT, mm	207
APPROXIMATE WEIGHT, kg	14.5

TERMINAL DATA	METRIC
TYPE	STD Terminal
TERMINAL HEIGHT, mm	18.5±1.5
BOTTOM DIAMETER, mm	Positive: 19.5+0/-0.3 Negative: 17.9+0/-0.3
TAPER	1:9
POLARITY	A

**CAPACITY SPECIFICATIONS**

COLD CRANKING AMPS (CCA)	600 CCA
AMPERE-HOUR AT 20-HOUR CAPACITY	95 Ah
RESERVE CAPACITY (RC)	160 mins

MAX CHARGING VOLTAGE	7.4 V at 25°C
FLOAT CHARGING VOLTAGE	6.7 V – 6.9V at 25°C
OPERATING TEMPERATURE	-40°C to 80°C** Optimal Temperature: 25°C ± 5°C

\*Warranty terms and conditions apply.

\*\*Based on normal engine bay temperature.

(Note) The company reserves the right to update the information above without prior notice.